



3 phase in / 3 phase out

5- 80 kVA

DS POWER 110 SERIES

UNINTERRUPTIBLE POWER SUPPLIES

IGBT RECTIFIER DSP CONTROL

The new DS Power range UPS uses the latest DSP technology to be programmed to suit a wide variety of electrical environments without impeding its performance. With the DS Power range, efficiency, reliability and functionality are enhanced to levels unattainable with the old analogue technology. This technology does not only create significant increase in MTBF, but the capability of DSP to accurately manipulate signals at very high speed permits all the UPS subsystems to be controlled with greatly increased precision.

GENERAL SPECIFICATIONS

- Transformerless UPS topology
- Low input current total harmonic distortion (THD)
- High input power factor
- High efficiency up to 94%
- Cold start function
- Static and maintenance by-pass switch
- Output short circuit and overload protection
- External REPO switch input
- 192 events memory (192 events 4500 alarms)
- Clock and calender (battery supported)
- Automatic battery test, remaining battery time indicator
- Temperature compensated charge system (optional)
- 2 RS232 serial ports and 12 dry contact outputs
- 3 DSP controlled modular structure
- Optional SNMP and MODBUS adaptors
- Optional graphical panel
- Optional USB flash memory
- Full digital structure
- Small footprint
- Ecomode operation (optional)
- Fewer electronic components
- Output current limiting
- Advanced diagnostics for the input
- Selectable input/output voltage/frequency/range
- Split by-pass input (second input)
- Output DC leakage protection
- Separate DSP for inverter control
- Separate DSP for the PFC
- 3 level battery protection
- High charge current capacity
- Charge/discharge current indicator
- Advanced remote control
- Manufactured according to EC Directive; EN62040
- 10 years spare parts support
- 2 years warranty



CE

Tescom®



5 - 80 kVA

TECHNICAL SPECIFICATIONS



MODEL	DS305-110	DS310-110	DS315-110	DS320-110	DS330-110	DS340-110	DS350-110	DS360-110	DS380-110				
Power (kVA)	5	10	15	20	30	40	50	60	80				
INPUT													
Voltage	200/208 VAC 3P + N, ± 20% (220VAC +15% -25%)												
Frequency	50Hz / 60Hz , ± %5												
Power factor (at 100% load)	≥ 0.99												
THDI (*)	≤ %4												
By-pass voltage	200/208 VAC 3P + N, ± 20% (220VAC +15% -25%)												
Protection	Fuses, voltage tolerance, frequency tolerance, input power limit												
OUTPUT													
Power (kW)	4,5	9	13,5	18	27	36	45	54	72				
Power factor	0,9												
Voltage	200/208/220 VAC 3P + N, ± 1%												
Frequency	50Hz / 60Hz												
Frequency tolerance	Line synchronized: ± 2% / Free running: ± 0,1%												
Efficiency (at 100% load)	up to 94%												
Crest factor	3:1												
Overload protection	100-125% for 10min, 125-150% for 1min, >150% load: by-pass												
Other protections	Advanced short circuit, voltage tolerance, DC balance, regenerative load, current limiting												
THD	< 3% (at 100% linear load)												
BATTERIES													
Type	VRLA AGM / GEL / NiCd												
Nominal voltage	± 192 VDC for 200/208VAC (± 216 VDC for 220VAC)												
Float / End of disch. voltage	± 216 VDC / ± 160 VDC for 200/208VAC (± 243 VDC / ± 180VDC for 220VAC)												
Battery housing	Internal							External					
Battery ambient temp.	25°C												
Protections	3 level alarm, battery fuses, charging current limit, temperature compensation (optional)												
Automatic testing	Standard every 72 hours(adjustable)												
GENERAL													
Standards	EMC(2004/108/EC) / LVD(2006/95/EC) - EN62040-1, EN62040-2, EN60950												
User interface	4 lines LCD panel, Mimic leds, 5 vector buttons, Buzzer, graphical touch-panel (opt.)												
Indicators	P-N voltage, P-P voltage, Current, Power, Crest factor, Frequency, PF, Service time												
Advanced	Self diagnostics, 4 maintenance time indicators, Calibration over RS232												
Communication	2 x RS232 serial ports, 4 standard and 8 optional DRY contact alarm relays												
Inputs	EPO input, Interactive battery panel input, Genset input												
Genset kit	Standard (programmable)												
Software	Standard T-Mon UPS Management Software (3 clients + 1 server management)												
Alarm logging	Standard; with time & date 192 events, (optional 512 events)												
Protections	Power module over-temperature, Over current, Temperature high alarm												
Temperature range	0°C - 40°C												
Protection degree	IP20												
Humidity	90% max (noncondensed)												
Altitude	< 1000m above sea level												
Acoustic noise	≤ 57dBA	≤ 62 dBA			≤ 64 dBA			≤ 68 dBA					
Weight (kg.)	87	91	100	173	180	194	216	216	258				
Dimensions (mm) HxWxD	1035x400x810					1440x515x850							
OPTIONS													
Input / Output voltage	Other special input/output voltages												
Transformer	Galvanic isolation transformer at the input & output												
Software	T-Mon Admin Multi UPS monitoring, T-Mon Server 50-100-200 clients, DLOG log loader												
Comm. adaptors	SNMP, MODBUS, RS485, Remote Panel												
Parallel operation	Up to 8 UPS												

(*) Depending on power and input/output conditions